



(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
27.11.2002 Bulletin 2002/48

(51) Int Cl.7: **B60K 6/04, B60L 11/12**

(21) Application number: 02253322.8

(22) Date of filing: 13.05.2002

(84) Designated Contracting States:
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
 MC NL PT SE TR**
 Designated Extension States:
AL LT LV MK RO SI

(30) Priority: 24.05.2001 US 865100

(71) Applicant: **Ford Global Technologies, Inc.**
Dearborn, Michigan 48124 (US)

(72) Inventors:


- Kuang, Ming Lang
Canton, Michigan 48188 (US)
- Patil, Prabhakar B.
Southfield, Michigan 48076 (US)
- McCarthy, James Paul
Milford, Michigan 48380 (US)

(74) Representative: Messulam, Alec Moses et al
A. Messulam & Co. Ltd.,
43-45 High Road
Bushey Heath, Bushey, Herts WD23 1EE (GB)

(54) **A control strategy for a hybrid vehicle while traveling in reverse**

(57) A controller 46 and control strategy for a hybrid electric vehicle is disclosed in which the control strategy controls a split powertrain hybrid electric vehicle (HEV)

when the vehicle is traveling in reverse, a battery state-of-charge is low and the powertrain is configured to only use the motor 38 while traveling in reverse



-Fig-1

Description

[0001] The present invention relates generally to a hybrid electric vehicle (HEV), and specifically to a strategy to control a split powertrain HEV while the vehicle travels in reverse and vehicle state-of-charge (SOC) is low.

[0002] The need to reduce fossil fuel consumption and emissions in automobiles and other vehicles predominately powered by internal combustion engines (ICES) is well known. Vehicles powered by electric motors attempt to address these needs. Another alternative solution is to combine a smaller ICE with electric motors into one vehicle. Such vehicles combine the advantages of an ICE vehicle and an electric vehicle and are typically called hybrid electric vehicles (HEVs). See generally, U.S. Pat. No. 5,343,970 to Severinsky.

[0003] The HEV is described in a variety of configurations. Many HEV patents disclose systems where an operator is required to select between electric and internal combustion operation. In other configurations, the electric motor drives one set of wheels and the ICE drives a different set.

[0004] Other, more useful, configurations have developed. For example, a series hybrid electric vehicle (SHEV) configuration is a vehicle with an engine (most typically an ICE) connected to an electric motor called a generator. The generator, in turn, provides electricity to a battery and another electric motor, called a traction motor. In the SHEV, the traction motor is the sole source of wheel torque. There is no mechanical connection between the engine and the drive wheels. A parallel hybrid electrical vehicle (PHEV) configuration has an engine (most typically an ICE) and an electric motor that work together in varying degrees to provide the necessary wheel torque to drive the vehicle. Additionally, in the PHEV configuration, the motor can be used as a generator to charge the battery from the power produced by the ICE.

[0005] A parallel/series hybrid electric vehicle (PSHEV) has characteristics of both PHEV and SHEV configurations and is sometimes referred to as a "powersplit" configuration. In one of several types of PSHEV configurations, the ICE is mechanically coupled to two electric motors in a planetary gear-set transaxle. A first electric motor, the generator, is connected to a sun gear. The ICE is connected to a carrier gear. A second electric motor, a traction motor, is connected to a ring (output) gear via additional gearing in a transaxle. Engine torque can power the generator to charge the battery. The generator can also contribute to the necessary wheel (output shaft) torque if the system has a one-way clutch. The traction motor is used to contribute wheel torque and to recover braking energy to charge the battery. In this configuration, the generator can selectively provide a reaction torque that may be used to control engine speed. In fact, the engine, generator motor and traction motor can provide a continuous variable transmission (CVT) effect. Further, the HEV presents an opportunity to better control engine idle speed over conventional vehicles by using the generator to control engine speed.

[0006] The desirability of combining an ICE with electric motors is clear. There is great potential for reducing vehicle fuel consumption and emissions with no appreciable loss of vehicle performance or drive-ability. The HEV allows the use of smaller engines, regenerative braking, electric boost, and even operating the vehicle with the engine shutdown. Nevertheless, new ways must be developed to optimize the HEV's potential benefits.

[0007] One such area of HEV development is controlling a powersplit HEV while traveling in reverse. In the prior art, a reverse gear in a transmission is engaged when the vehicle operator moves a shift lever to the reverse, or "R", position. In an HEV, a variety of powertrain configurations based on vehicle conditions can require new strategies to move the vehicle in reverse.

[0008] A strategy for moving an HEV in reverse is known in the prior art. See U.S. Patent No. 5,847,469 to Tabata et al. Tabata et al. describes an HEV using a conventional transmission to power the vehicle's wheels. The patent describes a system for the electric traction motor alone to reverse the direction of the vehicle without reversing the rotation of the motor so long as there is enough battery charge. Otherwise, the engine is started to assist the motor.

[0009] A conventional transmission with a reverse gear could be considered an inefficient and unnecessary complication and expense in a split powertrain HEV. Alternatively, the electric traction motor alone is used to propel the vehicle in reverse direction. When moving in reverse, the ring gear torque, resulting from engine output, goes against the vehicle moving in reverse. Thus, using the engine while the vehicle is in reverse is undesirable. Nevertheless, if battery state-of-charge (SOC) is low, the engine may need to run to power a generator to charge the battery and allow the motor to operate.

[0010] Unfortunately, no strategy is known to control a split powertrain HEV while the vehicle travels in reverse with the engine running because the battery state-of-charge (SOC) is low and the electric traction motor requires electricity produced by the generator for reverse motive power.

[0011] According to a first aspect of the invention there is provided a powersplit hybrid electric vehicle powertrain comprising an engine, a traction motor, a generator motor, an electric energy storage device for storing electric energy, the electric energy storage device being connected to the traction motor to power the traction motor and to the generator motor to receive energy generated by the generator motor characterised in that the powertrain further comprises of a power transmission device including at least one forward drive position to move the vehicle in a forward direction and at least one reverse drive position to move the vehicle in a reverse direction, the power transmission device being

connected to the engine, the traction motor, and the generator motor, a driver operable drive position selector comprising a reverse drive mode and a vehicle system controller comprising a reverse drive mode controller activated when the drive position selector is in the reverse drive mode, wherein the reverse drive mode controller is operable to prevent the electric energy storage device state-of-charge from continuously falling while meeting driver demand.

[0012] Preferably, the reverse drive mode controller may be operable to determine whether the engine and generator motor are running; to calculate a benefit power from the engine if the engine and the generator motor are running; to compare the benefit power with a first predetermined value; to determine whether a driver torque request plus the traction motor torque is greater than a predetermined maximum traction motor torque if the benefit power is greater than or equal to the first predetermined value; to calculate a new generator motor torque request if the determination of whether the driver torque request plus the generator motor torque is greater than the predetermined maximum torque; to determine whether the new generator motor torque request is greater than or equal to a second predetermined value; to calculate a new generator motor speed for the new generator motor torque request if the new generator motor torque request is greater than or equal to the second predetermined value; to determine whether the new generator motor speed is less than or equal to a maximum generator motor speed and to determine a new generator motor torque request if the new generator motor speed is less than or equal to the maximum generator motor speed.

[0013] The benefit power from the engine may be determined by the equation:

$$\eta_g \tau_e \omega_e - (1/\eta_m - \eta_g) \tau_r \omega_r.$$

[0014] The calculation of the new generator motor torque request may be determined by the equation:

$$\tau_{g_req} = (\tau_{m_max} - \tau_{d_req@ m})/T.$$

[0015] The new traction motor torque request may be determined by adding the driver torque request to the new generator motor torque request.

[0016] The reverse drive mode controller may further comprise of a stop engine command if the benefit power is less than the first predetermined value.

[0017] The reverse drive mode controller may further comprise of a stop engine command if the new generator motor torque request is less than the second predetermined value.

[0018] The reverse drive mode controller may further comprise of a stop engine command if the new generator motor speed is greater than a maximum generator motor speed.

[0019] According to a second aspect of the invention there is provided a method to control reverse drive mode in a hybrid electric vehicle when a drive position selector is in a reverse drive mode to prevent an electric energy storage device state-of-charge from continuously falling while meeting driver demand, characterised in that the method comprises of the steps of determining whether an engine and generator motor are running; calculating a benefit power from the engine if the engine and the generator motor are running; comparing the benefit power with a first predetermined value; determining whether a driver torque request plus generator motor torque is greater than a predetermined maximum traction motor torque if the benefit power is greater than or equal to the first predetermined value; calculating a new generator motor torque request if the step of determining whether the driver torque request plus the generator motor torque is greater than the predetermined maximum traction motor torque; determining whether the new generator motor torque request is greater than or equal to a second predetermined value; calculating a new generator motor speed for the new generator motor torque request if the new generator motor torque request is greater than or equal to the second predetermined value; determining whether the new generator motor speed is less than or equal to a maximum generator motor speed and determining a new traction motor torque request if the new generator motor speed is less than or equal to the maximum generator motor speed.

[0020] The step of determining the benefit power from the engine may use the equation:

$$\eta_g \tau_e \omega_e - (1/\eta_m - \eta_g) \tau_r \omega_r.$$

[0021] The calculation of the new generator motor torque request may be determined by the equation:

$$\tau_{g_req} = (\tau_{m_max} - \tau_{d_req@ m})/T.$$

[0022] The step of determining the new traction motor torque request may be achieved by adding the driver torque

request to the new generator motor torque request.

[0023] The method may further comprise the step of stopping the engine if the benefit power is less than the first predetermined value.

[0024] The method may further comprise the step of stopping the engine if the new generator motor torque request is less than the second predetermined value.

[0025] The method may further comprise the step of stopping the engine if the new generator motor speed is greater than the maximum generator motor speed.

[0026] The invention will now be described by way of example with reference to the accompanying drawing of which:-

Figure 1 illustrates a general hybrid electric vehicle (HEV) configuration;

Figure 2 illustrates the power flow within the powertrain; and

Figure 3 illustrates the strategy of the present invention for an HEV while travelling in reverse.

[0027] The present invention relates to electric vehicles and, more particularly, to hybrid electric vehicles (HEVs). Figure 1 demonstrates just one possible configuration, specifically a parallel/series hybrid electric vehicle (powersplit) configuration.

[0028] In a basic HEV, a planetary gear set 20 mechanically couples a carrier gear 22 to an engine 24 with a one-way clutch 26 to prevent the engine from rotating in a counter clock wise (CCW) direction. The planetary gear set 20 also mechanically couples a sun gear 28 to a generator motor 30 and a ring (output) gear 32. The generator motor 30 also mechanically links to a generator brake 34 and is electrically linked to an electric energy storage device (battery) 36 to receive electric energy converted from mechanical energy by the generator motor 30. A traction motor 38 is mechanically coupled to the ring gear 32 of the planetary gear set 20 via a second gear set 40 and is electrically linked to the battery 36. The ring gear 32 of the planetary gear set 20 and the traction motor 38 are mechanically coupled to drive wheels 42 via an output shaft 44. The mechanical coupling represents collectively a power transmission device, the power transmission device being connected to the engine 24, the traction motor 38 and the generator motor 30.

This power transmission device can be configured to have at least one forward drive position to move the HEV in a forward direction and at least one reverse drive position to move the HEV in a reverse direction. A driver operated drive position selector (gear selector) (not shown) determines whether the vehicle is to move in the reverse direction. [0029] The planetary gear set 20, splits the engine 24 output energy into a series path from the engine 24 to the generator motor 30 and a parallel path from the engine 24 to the drive wheels 42. Engine 24 speed can be controlled by varying the split to the series path while maintaining the mechanical connection through the parallel path. The traction motor 38 augments the engine 24 power to the drive wheels 42 on the parallel path through the second gear set 40. The traction motor 38 also provides the opportunity to use energy directly from the series path, essentially running off power created by the generator motor 30. This reduces losses associated with converting energy into and out of chemical energy in the battery 36 and allows all engine 24 energy, minus conversion losses, to reach the drive wheels 42.

[0030] A vehicle system controller (VSC) 46 controls many components in this HEV configuration by connecting to each component's controller. An engine control unit (ECU) (not shown) connects to the engine 24 via a hardwire interface. The ECU and VSC 46 can be based in the same unit, but are actually separate controllers. The VSC 46 communicates with the ECU, as well as a battery control unit (BCU) 50 and a transaxle management unit (TMU) 52 through a communication network such as a controller area network (CAN) 54. The BCU 50 connects to the battery 36 via a hardwire interface. The TMU 52 controls the generator motor 30 and traction motor 38 via a hardwire interface.

[0031] All vehicles require movement in a reverse direction from time to time. Such movement usually begins with a driver manually shifting a gear selector to a reverse (or "R") position. In the powertrain configuration of the present invention, the engine 24 does not provide primary drive to the vehicle while traveling in reverse. There is no true rear drive shifting means in that there is no discrete exchange of power flow elements that produces a reverse range as opposed to a forward range. In fact, torque from the engine 24 while in reverse would work against the traction motor 38 traveling in reverse. Nevertheless, to operate the traction motor 38 in a reverse rotation, the engine 24 may be needed to charge the battery 36 if a low state-of-charge (SOC) exists. During engine 24 operation to generate the electricity, the engine 24 would produce torque through the second gear set 40 that would attempt to drive the vehicle in a forward direction. It is only by the balance of the relative forward and reverse torques that the net vehicle rearward torque is augmented.

[0032] For example, if the vehicle is moving in reverse at a certain vehicle speed (equivalent to ω_r), the traction motor's 38 output power required for the vehicle speed is P_r . Also assume the engine 24 is running at a constant power output ($\tau_e \omega_e$), and both efficiencies of the planetary gear set 20 and the second gear set 40 are one. The resulted ring output gear 32 torque from the engine 24 torque (τ_e) is $\tau_r = \tau_e / (1 + p)$. p is the gear ratio between the sun gear 28 and

the ring gear 32 (N_g/N_r). η_g and η_m are the efficiencies for the generator motor and the traction motor respectively. The power flow within the powertrain under these assumptions is illustrated in Figure 2. The following symbols listed below will assist in understanding the present invention:

5	$\omega_r =$	ring gear speed
	$\omega_e =$	engine speed
	$P_v =$	output power
	$\tau_e \omega_e =$	engine power output
	$\tau_e =$	engine torque
10	$\tau_r =$	ring gear torque
	$\rho =$	gear ratio between sun gear and ring gear
	$N_s =$	number of teeth in sun gear
	$N_r =$	number of teeth in ring gear
	$\eta_g =$	overall efficiency for generator
15	$\eta_m =$	overall efficiency for motor
	$P_{batt} =$	power charging the battery
	$\eta_g \tau_e \omega_e =$	engine's electrical output power (through generator)
	$P_v / \eta_m =$	motor's input power (electrical)
	$(1/\eta_m - \eta_g) \tau_r \omega_r =$	power circulation loss between motor and generator
20	$\tau_{d_req@ m} =$	driver's torque request at the motor
	$\tau_g =$	generator torque
	$\omega_g =$	generator speed
	$W_{benefit} =$	benefit power from the engine
	$K_w =$	a predetermined $W_{benefit}$ value
25	$\tau_{m_max} =$	maximum motor torque
	$\tau_{g_req} =$	generator torque request
	$\tau_{g_min} =$	generator torque request minimum
	$\omega_{g_cal} =$	calculated generator speed
	$\omega_{g_max} =$	maximum generator speed.
30	$T =$	gear ratio from generator to motor

[0033] The power flow illustrated in Figure 2 demonstrates part of the traction motor 38 output ($\tau_r \omega_r$ required to overcome the engine 24 output at the ring gear 32) is also part of the generator motor 30 input, which generates electricity. Clearly, this is a power circulation between the traction motor 38 and the generator motor 30, which results in power circulation loss in the powertrain system.

[0034] The power charging the battery 36 is P_{batt} and is shown by:

$$P_{batt} = \eta_g (\tau_e \omega_e + \tau_r \omega_r) - (P_v + \tau_r \omega_r) / \eta_m ,$$

or

$$P_{batt} = \eta_g \tau_e \omega_e - P_v / \eta_m - (1/\eta_m - \eta_g) \tau_r \omega_r .$$

[0035] In this example, $\eta_g \tau_e \omega_e$ is the engine's 24 electrical output power (through the generator motor 30), P_v / η_m is the traction motor's 38 input power (electrical) required to propel the vehicle, and $(1/\eta_m - \eta_g) \tau_r \omega_r$ is the power circulation loss between the traction motor 38 and generator motor 30. If the power circulation loss is greater than or close to the engine's 24 electrical output power, there is no benefit to operate the engine 24 since the engine 24 output only generates heat in the traction motor 38 and generator motor 30, and does not charge the battery 36.

[0036] To ensure the benefit of operating the engine 24 when the vehicle travels in reverse and the battery 36 SOC is low, it is necessary for the VSC 46 to control the powertrain system properly to avoid the result illustrated above.

[0037] The present invention is a control strategy within the VSC 46 to efficiently control the illustrated powersplit HEV powertrain system when the vehicle travels in reverse and the battery 36 SOC is low. The reverse drive mode controller is activated when the drive position selector is in the reverse drive mode. The present invention operates the powertrain system efficiently and prevents the battery 36 SOC from continuously falling while meeting the driver's demand. The strategy is illustrated in Figure 3.

[0038] At Step 60, the reverse drive mode controller strategy first reads the following vehicle inputs 58: PRND po-

sition, driver's torque request at the motor ($\tau_{d_req@m}$), generator torque (τ_g) and speed (ω_g), vehicle speed (to calculate ring gear speed ω_r), engine speed (ω_e), and engine and generator status. PRND position represents a driver operated drive position selector, or gear selector, (not shown) that is manually shifted by the vehicle driver. If the gear selector is in the "R" position, the driver has requested the vehicle to move in reverse.

[0039] At Step 62, the strategy next determines if the gear selector is in the "R" position. If no, the strategy ends.

[0040] If "R" is selected at Step 62, the strategy next determines if both the engine 24 and generator motor 30 are running at Step 64. If no, the strategy ends. If both the engine 24 and generator motor 30 are running at Step 64, the strategy calculates the benefit power from the engine 24 $W_{benefit}$ at Step 66 using the equation $W_{benefit} = \eta_g \tau_e \omega_e - (1/\eta_m \eta_g) \tau_r \omega_r$.

[0041] Next the strategy determines at Step 68 whether the $W_{benefit}$ is greater than or equal to a first predetermined value K_w . This value indicates it is desirable to run the engine 24 to charge the battery 36.

[0042] If $W_{benefit}$ is greater than or equal to K_w at Step 68, the strategy next determines at Step 72 whether the sum of the driver's torque request at motor ($\tau_{d_req@m}$) plus the generator motor 30 torque reflected at the motor shaft ($\tau_g T$, where T is the gear ratio from generator to motor and is well known in the prior art) is greater than the predetermined maximum motor torque (τ_{m_max}). If the $W_{benefit}$ is less than K_w , the strategy executes a stop engine process at Step 70 and ends the strategy.

[0043] If the sum is greater than the predetermined maximum motor torque at Step 72, the strategy calculates a new generator motor 30 torque request (τ_{g_req}) at Step 74 so that the driver's torque request is not compromised and the vehicle reverse acceleration performance meets driver demand. The calculation is as follows: $\tau_{g_req} = (\tau_{m_max} - \tau_{d_req@m}) / T$. Otherwise, the strategy proceeds to calculate a new traction motor 38 torque request (τ_{m_req}) at Step 76 using: $\tau_{m_req} = \tau_{d_req@m} + \tau_{g_req} T$ and the strategy ends.

[0044] Next, the strategy determines at Step 78 whether the new generator motor 30 torque request (τ_{g_req}) is greater than or equal to a second predetermined value (τ_{g_min}). This implies the generator motor's 30 torque can be accurately controlled. If (τ_{g_req}) is greater than or equal to the second predetermined value (τ_{g_min}) at Step 78, the strategy proceeds to determine the calculated generator motor 30 speed (ω_{g_cal}) for the given new generator motor 30 torque request at Step 80. Otherwise, the strategy proceeds to execute the stop engine process at Step 70 and ends the strategy. With the new generator motor 30 torque request (τ_{g_req}), a new engine 24 speed (ω_e) can be determined and then the calculated generator motor 30 speed (ω_{g_cal}) of Step 80 can be derived based on the new engine 24 speed and ring gear 32 speed (equivalent to present vehicle speed).

[0045] Next, at Step 82, the strategy determines whether the calculated generator motor 30 speed (ω_{g_cal}) is less than or equal to a predetermined maximum generator motor 30 speed (ω_{g_max}). If yes, the strategy proceeds to Step 76 (described above) to determine the new traction motor 38 torque request to meet the driver's demand. This motor torque request compensates the ring gear 32 torque resulted from the engine 24 output to meet the driver's demand. If the calculated generator motor 30 speed (ω_{g_cal}) is greater than the maximum generator motor 30 speed (ω_{g_max}) at Step 82, the strategy proceeds to execute the stop engine process at Step 70 and the strategy ends.

[0046] The above-described embodiment of the invention is provided purely for purposes of example. Many other variations, modifications, and applications of the invention may be made.

Claims

1. A powersplit hybrid electric vehicle powertrain comprising an engine (24), a traction motor (38), a generator motor (30), an electric energy storage device (36) for storing electric energy, the electric energy storage device (36) being connected to the traction motor (38) to power the traction motor (38) and to the generator motor (30) to receive energy generated by the generator motor (30) **characterised in that** the powertrain further comprises of a power transmission device (20) including at least one forward drive position to move the vehicle in a forward direction and at least one reverse drive position to move the vehicle in a reverse direction, the power transmission device being connected to the engine (24), the traction motor (38), and the generator motor (30), a driver operable drive position selector comprising a reverse drive mode and a vehicle system controller (46) comprising a reverse drive mode controller activated when the drive position selector is in the reverse drive mode, wherein the reverse drive mode controller is operable to prevent the electric energy storage device state-of-charge from continuously falling while meeting driver demand.
2. A powertrain as claimed in claim 1 wherein the reverse drive mode controller is operable to determine whether the engine and generator motor are running; to calculate a benefit power from the engine if the engine and the generator motor are running; to compare the benefit power with a first predetermined value; to determine whether a driver torque request plus the traction motor torque is greater than a predetermined maximum traction motor torque if the benefit power is greater than or equal to the first predetermined value; to calculate a new generator motor

torque request if the determination of whether the driver torque request plus the generator motor torque is greater than the predetermined maximum torque; to determine whether the new generator motor torque request is greater than or equal to a second predetermined value; to calculate a new generator motor speed for the new generator motor torque request if the new generator motor torque request is greater than or equal to the second predetermined value; to determine whether the new generator motor speed is less than or equal to a maximum generator motor speed and to determine a new generator motor torque request if the new generator motor speed is less than or equal to the maximum generator motor speed.

3. A powertrain as claimed in claim 2 wherein the new traction motor torque request is determined by adding the driver torque request to the new generator motor torque request.

4. A method to control reverse drive mode in a hybrid electric vehicle when a drive position selector is in a reverse drive mode to prevent an electric energy storage device state-of-charge from continuously falling while meeting driver demand, **characterised in that** the method comprises of the steps of determining whether an engine and generator motor are running; calculating a benefit power from the engine if the engine and the generator motor are running; comparing the benefit power with a first predetermined value; determining whether a driver torque request plus generator motor torque is greater than a predetermined maximum traction motor torque if the benefit power is greater than or equal to the first predetermined value; calculating a new generator motor torque request if the step of determining whether the driver torque request plus the generator motor torque is greater than the predetermined maximum traction motor torque; determining whether the new generator motor torque request is greater than or equal to a second predetermined value; calculating a new generator motor speed for the new generator motor torque request if the new generator motor torque request is greater than or equal to the second predetermined value; determining whether the new generator motor speed is less than or equal to a maximum generator motor speed and determining a new traction motor torque request if the new generator motor speed is less than or equal to the maximum generator motor speed.

5. A method as claimed in claim 4 wherein the step of determining the benefit power from the engine uses the equation:

$$\eta_g \tau_e \omega_e - (1/\eta_m - \eta_g) \tau_r \omega_r.$$

6. A method as claimed in claim 4 or in claim 5 wherein the calculation of the new generator motor torque request is determined by the equation:

$$\tau_{g_req} = (\tau_{m_max} - \tau_{d_req@m}) / T.$$

7. A method as claimed in any of claims 4 to 6 wherein the step of determining the new traction motor torque request is achieved by adding the driver torque request to the new generator motor torque request.

8. A method as claimed in any of claims 4 to 7 further comprising the step of stopping the engine if the benefit power is less than the first predetermined value.

9. A method as claimed in any of claims 4 to 8 further comprising the step of stopping the engine if the new generator motor torque request is less than the second predetermined value.

10. A method as claimed in any of claims 4 to 9 further comprising the step of stopping the engine if the new generator motor speed is greater than the maximum generator motor speed.




Fig-1




Fig-2

